PULSATING TORQUE MOUNTING TOOL YOKOTA

Yokota A battery pulse machine is the solution for applications where cables or hoses are in the way, giving full freedom of movement. The ergonomic design and small weight in combination with low reaction forces from the tool provide a safe workplace environment for the operator. The YZ-N series makes it extremely easy to access the screw joint. For tightening bolts from M6 up to M10 with torque levels up to 65 Nm, with very high installation speeds and remarkably low reaction forces. The engine speed is adjusted via a knob offering 4 positions (2000, 3000, 4000, 4800 rpm). The combination of adjustment via the relief valve and engine speed adjustment give the opportunity to customise the settings for specific screw joints, hard or soft. The pulse machine is equipped with an electric (brushless) motor. LED indication for overheating, engine/driver routine faults and warning for low battery capacity. NOTE: Battery and charger not included, all accessories sold separately, see below.

Code no.	**(27292-0109)**	**(27292-0208)**	**(27292-0307)**
Short description	BATTERY IMP. WRENCH YZ-N600A-Z	BATTERY IMP. WRENCH YZ-N600-Z	BATTERY IMP. WRENCH YZ-N800A-Z
Manufacturer´s description	YZ-N600A-Z	YZ-N600-Z	YZ-N800A-Z
Torque range, max	20 Nm	25 Nm	30 Nm
Torque range, min	7 Nm	8 Nm	7 Nm
Type	Bit type	Bit type	Bit type
Screw capacity	M6	M6	M6-M8
Speed	2000-4800 RPM	2000-4800 RPM	2000-4800 RPM
Vibration (ISO 28927-2)	<2.5 m/s2	<2.5 m/s2	<2.5 m/s2
Sound level (ISO 15744)	72 dB (A)	72 dB (A)	75 dB (A)
Weight	1 kg	1 kg	1,1 kg
Battery	18 V/2 Ah	18 V/2 Ah	18 V/2 Ah
Socket drive	1/4 hex	3/8	1/4 hex
Qty/pack	1 PCS	1 PCS	1 PCS
Packaging	1 PCS	1 PCS	1 PCS

Code no.	**(27292-0406)**	**(27292-0505)**	**(27292-0604)**
Short description	BATTERY IMP. WRENCH YZ-N800-Z	BATTERY IMP. WRENCH YZ-N900-Z	BATTERY IMP. WRENCH YZ-N950-Z
Manufacturer´s description	YZ-N800-Z	YZ-N900-Z	YZ-950-Z
Torque range, max	35 Nm	60 Nm	65 Nm
Torque range, min	9 Nm	16 Nm	20 Nm
Type	Bit type	Bit type	Bit type
Screw capacity	M6-M8	M8-M10	M8-M10
Speed	2000-4800 RPM	2000-4800 RPM	2000-4800 RPM
Vibration (ISO 28927-2)	<2.5 m/s2	<2.5 m/s2	<2.5 m/s2
Sound level (ISO 15744)	75 dB (A)	77 dB (A)	78 dB (A)
Weight	1,1 kg	1,2 kg	1,3 kg
Battery	18 V/2 Ah	18 V/2 Ah	18 V/2 Ah
Socket drive	3/8	3/8	3/8
Qty/pack	1 PCS	1 PCS	1 PCS
Packaging	1 PCS	1 PCS	1 PCS

Code no.	**Accessories**	**Article description**	**Packaging**
(27292-0109)	(27292-1008)	BATTERY LI-ON 18V 2AH BPL-1820	1 PCS
(27292-0109)	(27292-1107)	BATTERY CHARGER 18V BC0075G	1 PCS
(27292-0208)	(27292-1008)	BATTERY LI-ON 18V 2AH BPL-1820	1 PCS
(27292-0208)	(27292-1107)	BATTERY CHARGER 18V BC0075G	1 PCS
(27292-0307)	(27292-1008)	BATTERY LI-ON 18V 2AH BPL-1820	1 PCS
(27292-0307)	(27292-1107)	BATTERY CHARGER 18V BC0075G	1 PCS
(27292-0406)	(27292-1008)	BATTERY LI-ON 18V 2AH BPL-1820	1 PCS
(27292-0406)	(27292-1107)	BATTERY CHARGER 18V BC0075G	1 PCS
(27292-0505)	(27292-1008)	BATTERY LI-ON 18V 2AH BPL-1820	1 PCS
(27292-0505)	(27292-1107)	BATTERY CHARGER 18V BC0075G	1 PCS
(27292-0604)	(27292-1008)	BATTERY LI-ON 18V 2AH BPL-1820	1 PCS
(27292-0604)	(27292-1107)	BATTERY CHARGER 18V BC0075G	1 PCS