BATTERY CHARGER SPI15

Schumacher fully automatic battery charger/support unit designed for all types of car batteries. Regular mode: For charging and maintain. Power supply mode: Maintains stable voltage at 13,6V and prevent discharged batteries during service or sitting idle in showrooms.

Code no.	**26476-0901**
Short description	BATTERY CHARGER SPI1015S 12V
Enclosure protection class	IP 20
Battery capacity	10-230 Ah
Mains voltage cable	2 m
Weight	1,7 kg
Charging current max. 12 V/low setting	15 A
Width	240 mm
Height	96 mm
Battery type	AGM GEL MF Open
Length	225 mm
Battery size	12 V
Charging current continuous operation, average	15 A
Manufacturer´s description	SPI15S
Voltage	220-240 AC
Ambient temperature	-20 – +50
Fuse	10 A
Qty/pack	1 PCS
Packaging	1 PCS

BATTERY CHARGER SPI1224

Schumacher fully automatic 12V/24V charger. Suitable for all 12V and 24V vehicles. Features 2 selectable modes: Regular charge and Recovery mode (for deep discharged or sulfated batteries). Reverse polarity protection, thermal runway protection and automatic shut-off.

Code no.	**26476-0802**
Short description	BATTERY CHARGER SPI1224 12/24V
Manufacturer´s description	SPI1224
Battery size	12/24 V
Battery capacity	10-230 Ah
Battery type	AGM GEL MF Open
Charging current continuous operation, average	15 A
Charging current max. 12 V/low setting	15 A
Voltage	220-240 AC
Ambient temperature	-20 – +50
Mains voltage cable	2 m
Fuse (inert)	10 A
Enclosure protection class	IP 20
Length	225 mm
Width	240 mm
Height	96 mm
Weight	1,75 kg
Qty/pack	1 PCS
Packaging	1 PCS